

RF750

**STREAMLINE YOUR
WORKFLOW AND
MAXIMIZE EFFICIENCY
WITH UHF TECHNOLOGY
—MADE FOR PM75**



Retail



Industrial Production
Process Control



Logistics /
Warehouse Management



Medical / Pharmacy

Specifications

PHYSICAL CHARACTERISTICS

Dimensions

Standard 83.05 mm W x 160.5 mm L x 168.25 mm H

Weight

471.6g with standard battery (only RF750)

Power

Battery 3,250 mAh 3.6V Li-ion, removable

Buttons

Trigger, Power, Trigger Mode, Connection Mode

Standard Communications

USB interface

Power Supply

5V/2A adaptor

Notification

Charging LED, Status LED, Connect-Mode, Trigger-Mode LED, Vibration

PERFORMANCE CHARACTERISTICS

Supported Protocol Standards

EPC Global UHF Class 1 Gen 2 V2 / ISO 18000-63

RFID Engine

Impinj® Indy® R2000

Nominal Read Range 6m+ (19.69ft+)

Fastest Read Rate up to 900 tags per second

Frequency / RF Output

EU: 865MHz ~ 868MHz
= <30dBm (± 0.3dBm)
US: 902MHz ~ 928MHz
= <30dBm (± 0.3dBm)

Memory

RAM 160 KB
ROM 1MB

USER ENVIRONMENT

Operating Temperature -10°C to 50°C

Storage Temperature -40°C to 70°C

Drop 1.5m to concrete

Rain / Dust Proof (Sealing) IP54

WIRELESS

Bluetooth Bluetooth Ver. 4.2 BR/EDR/BLE

NFC Tap-to-Pair

ACCESSORIES

Standard Accessories



AC/DC Power Adapter

Country Plug



USB Type-C Cable

Hand-Strap



Battery

Optional Accessories



Single Slot Cradle
(charging only)

4 Slot Battery Charger



Corporate Headquarters
Point Mobile Co., Ltd.
pm_sales1@pointmobile.com
+82 2 3397 7870

NA Headquarters
Point Mobile Americas LLC
info@pointmobileamericas.com
+1 425 780 4452

Europe Headquarters
Point Mobile Europe GmbH
info.pmeg@pointmobile.com
+49 6196 777 3666

China Headquarters
Point Mobile China
info@pointmobile.com.cn
+86 755 8869 1169

For more information, visit www.pointmobile.com